

Fiber Tape HX-328

HX-328 is based on PET film glass fiber material, high-strength two-way fiber tape, high viscosity performance, suitable for heavy cargo strapping and paper Packing, bundling, strengthening the sea during transportation Shipping cartons, courier bags tearing, etc.

Product Features:

Fiber Tape 328 is a transparent high-strength two-way fiber tape. Glass fiber filaments make this tape have better tensile strength than ordinary tape. It can be bundled together very well, and has the effect of two-way reinforcement and firmness. It has strong wear resistance, impact resistance and high holding force.

Storage conditions:

It is recommended to place it in a clean and dry place to prevent To prevent damage to the packaging, avoid and volatile solvents Put together, store at 4~26°C, The humidity is 40%~50%, and the stock is placed in rotation.

physical properties	Imperial Units	Metric Units	test method	
Strengthening methods	glass fiber			
glue	synthetic rubber			
Substrate	PET			
color	clear			
Total thickness	4.7 mils	0.12 mm	ASTM D-3652	GB/T7125
Peel force90°	83 oz/in	23N/25mm	ASTM D-3330	GB/T2792
Retention force	≥24h	≥24h	ASTM D-3654	GB/T4851
Tensile	101 lbs/in	450N/25mm	ASTM D-3759	GB/T7753
Elongation	3%	3%	ASTM D-3759	GB/T7753
low temperature	23°F	-5°C	BC/BD-220SE	BC/BD-220SE
high temperature	158°F	70°C	DHG-9055A	DHG-9055A

*Different specifications and sizes can be cut according to customer requirements

The above test results are the average value of laboratory test results. Our company does not guarantee the accuracy of these tests accuracy. Whether it is used alone or in conjunction with other manufacturers' products, our company does not performance, safety, suitability, whether expressed or implied. My company It is strongly recommended that customers carry out independent testing to understand the suitability of the product before using it. right by Our company does not assume any responsibility for any damage or injury caused by the use of the product.