

Marking Tape JSH130-1

High quality Soft PVC Film, coated with a rubber based adhesive, hand applicable

FEATURES:

- Rubber adhesive
- PVC carrier

STANDARD SIZES:

- Length: 30m, 33m
- Width: 48mm, 50mm
- Core ID: 76.2mm

BENEFITS:

- Black and other colors available
- Highly conformable

COLORS:

- Black White Yellow
- Red Blue Green
- Orange
 Violet
 Brown

*Other sizes and colors are available on request

Properties	Value	Unit	Test Method
Total thickness	0 130±0 025	mm	EN 1942
Tensile strength	≥18	N/cm	ISO 29864
Elongation at break	≥150	%	ISO 29864
Adhesion strength			ISO 29862
— to steel	≥1.0	N/cm	
Tack	≥6	#	GB/T 4852

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

Indicated for floor marking of sport courts, factories, offices, banks, mails, parking lots. It can also be used for marking clear and smocked glass, as well as identifying industrial facilities (oil, water, and other products pipes). Used for decorating and protecting.

STORAGE AND SHELF LIFE:

The shelf life of the product is one year when stored at $20-30^{\circ}$ C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical informaion and data menioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specificaion. Therefore, all statements, technical informaion and recommendaions concerning products sold or samples provided by Avery Dennison Yongle do not consitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its applicaion purposes.

