

PL2000 Foil backed Pavement Marking Tape

Description:

PL2000 foil backed pavement marking tapes are designed to stripe asphalt and concrete surfaces, parking garages, warehouse floors, factory floors, roads and any other area where removable delineation is needed. Our tape is simple to install with no special equipment or contractor required. It is as thick as normal parking lot paint and has a durable, reflective surface. The tape's aggressive adhesive and conformable foil backing insure that when properly applied your reflective white, yellow lines will remain in place. Durability depends on traffic flow and proper installation. The tape performs best on smooth surfaces where all of the tape can make contact with the surface. Parking lots or warehouses with moderate to light traffic often get years of service out of the tape. The tape will conform to a moderately rough surface but performs best on smooth surfaces.

Features:

High visibility; easy application; conformable to the substrate.

Application:

It is designed for temporary installations, such as traffic lane lines, road construction sites, detours and similar traffic control requirements.

Technical Data:

Items	Values		Units	Test methods
Color	PL2001/W	PL2002/Y	---	---
Overall Thickness	0.6	0.6	mm	ASTM-D-4325
Retro reflectivity	200	150	mcd·m-21x-1	ASTM-D-4061
Adhesion	15	15	N/25mm	ASTM-D-1000
Skid Resistance	45	45	BPN	ASTM-E-303



Performance Life:

It is recommended that each customer thoroughly evaluate LUDWAY Pavement Marking Tapes under the conditions in the specified location. LUDWAY Technologies makes no generalized performance claims.

Standard Dimension:

- Standard length: 33m, 50m.
- Standard width: 10cm, 15cm, 20cm; Or according to customer's requirement.
- available color: white, yellow, black.
- with liner.

Important notice:

The information, data and other statements are based on our testing results, the user should determine the suitability of the product for its intended use.