

## PL5010 Pavement Marking Tape

### Description:

PL5010 pavement marking tape is pre-made with synthetic rubber. It has smooth surface without beads. The tape uses a high quality polyurethane topcoat with a special release coating to make it easy to clean up by water or wet mop. It has an ability of self-cleaning and non-stickiness to dust and mud. The bottom is coated with a strong and weather resistant adhesive which improves the adhesion between road and tape. It is more durable than traditional PVC marking tape

### Features:

smooth surface; high tensile; strong weather resistance; easy application; self-cleaning; Pre-cut symbols and legends— standard and custom.

### Application:

It can be used for road marking in airport, shopping center, exhibition hall, workshop etc. It is applicable to various pavements of concrete, asphalt, cement, marble and walls.

### Technical Data:

Items	Values		Units	Test methods
Color	PL5011/W	PL5012/Y	---	---
Overall Thickness	1.0	1.0	mm	ASTM-D-4325
Adhesion	16	16	N/25mm	ASTM-D-1000
Water resistant	PASS			ASTM-E-303



### Performance Life:

The performance life of pavement markings will depend on the following:

·Traffic conditions · Snow removal practices · Pavement surfaces · Application techniques

It is recommended that each customer thoroughly evaluate LUDWAY pavement marking tapes under the conditions in the specified location. While experience has shown that when properly applied, these materials are highly effective traffic control devices, LUDWAY Technologies makes no generalized performance claims.

### Standard Dimension:

- Standard length:100m.
- Standard width:10cm, 15cm.
- available color: yellow

### Important notice:

The information, data and other statements are based on our testing results, the user should determine the suitability of the product for its intended use.