



## Liner less Low Voltage Tape (rubber tape) (HX-122)

### **Features:**

High quality polyamide velour's, in combination with an aging stable and strong acrylic based adhesive.

### **Applications:**

HX-122 is self-amalgamating, insulating mastic for insulating and sealing all types of overhead and direct buried electrical connections. It has super adhesion, anti-corrosion. For high voltage cable ends water sealing with continuous operating temperature up to 90°C. It is suitable for insulating protection of cable connection up to 1000V jacketed with vinyl tape. It is suitable for protecting cable joints, tube and cable ends.

### **Test Result:**

Property	Unit	Value	Test Method
Total Thickness	mm	0.76	ASTM-D-4325
Tensile Strength	psi	250	UL 510
Elongation at break	400	%	UL 510
Dielectric Strength	Kv/mm	20	UL 510

### **Other Property:**

- ◆ Color: Black
- ◆ Shelf life: 12 months when stored in original packing carton at 23°C×65%RH

### **Tape Size:**

- ◆ Standard Roll: 19mm/51mm×3.3m/6.7m
- ◆ Paper Core Inner Dia.: 38mm

### **Remarks:**

All the data above based on our testing, the user should do trial-application on the above products before coming into application, so as to witness and ensure suitability for user's special purpose and technique.

