

UM100N PVC Electrical Tape

Features:

Yongle UM100N PVC electrical tape is high quality Soft PVC Film, coated with a strong rubber based adhesive, hand applicable, 80°C.Flammability B,self-extinguishing. It is highly conformable and unaffected by most chemicals and moisture. Meet ROHS requirement it does not contain substances harmful to human body such as lead and cadmium.

Applications:

Electric insulation below 600V Insulating wrapping of electric wires and cables Marking of electric wires and cables Can be used indoor and outdoor

FEATURES:

PVC carrier

BENEFITS:

Rubber adhesive

· Black and other colors available

Brown

Highly conformable

• Meet RoHS & REACH

STANDARD SIZES:

COLORS:

Length: 18m, 20m, 25mm Black White Yellow Gray

Width: 19mm, 25mm Red Blue Green Violet

Core ID: 32mm, 38mm Other sizes and colors are available on request.

Technical Data:

Properties	Value	Unit	Test Method
Total thickness	0.100±0.02	mm	EN 1942
Tensile strength	≥11	N/cm	ISO 29864
Elongation at break	≥100	%	ISO 29864
Adhesion strength			ISO 29862
— to steel	≥1.0	N/cm	
— to backing	≥1.0	N/cm	
Flammability	B(self-extinguishing)		ASTM D1000
Dielectric Strength	≥40	KV/mm	IEC 60454

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

It is specifically designed for used for wrapping electric wires and cables etc. wrapped wires with a half-lap is best, The last layer should be no tension to prevent flagging.

STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

