

## 8888T PVC dry vinyl tape

YONGLE 8888T PVC dry vinyl tape, High quality non-adhesive soft PVC tape, hand and machine applicable, 105°C.

### FEATURES:

PVC carrier

### BENEFITS:

- Non-adhesive
- Flame retardant
- Highly conformable
- Soft PVC without adhesive
- Controlled, uniform unwind
- Securely Clings to itself
- Customized to the user's application
- Meet RoHS & REACH



### Technical Data:

Property	Unit	Typical data	Test Method
Total Thickness	mm	0.13±0.02	EN 1942
Tensile Strength	N/cm	> 20	ISO 29864
Elongation at break	%	> 250	ISO 29864
Adhesion strength			QCT-906(24fts/min)
---hand taping	Oz/19mm	20-40	
	N/19mm	5.5-11.1	
	Oz/25mm	20-45	
	N/25mm	5.5-12.5	
Flammability		2.0-6.0	GMW 16740/LV 312
Breakdown voltage	kV	6.0	ASTM D1000
Temperature rating	°C	B:-25-105	GMW 16740 / LV 312

Note: The listed values are required only and not intended to serve as product specifications

### Other Property:

Color: Black & White & Yellow

Other sizes and colors are available on request.

### **Tape Size:**

- ◆ Length: 33m, 40m
- ◆ Width: 19mm, 25mm
- ◆ Paper Core Inner Dia: 38mm

### **RECOMMENDED USES:**

YONGLE 8888T PVC dry vinyl tape, Designed for wrapping applications. For permanent protection of wire harnesses and cables. Also use for insulating and masking parts in the industrial electroplating industry.

### **STORAGE AND SHELF LIFE**

The shelf life of the product is one year when stored at 20-30 °C , max 65% relative humidity and out of direct sunlight, in original packaging.