

## JZ150N Harness Splicing Tape

High quality Soft-PVC-Film, coated with a strong rubber based adhesive, hand applicable, 85°C.

### FEATURES:

- PVC carrier
- Rubber adhesive

### BENEFITS:

- Black and Blue
- Highly conformable
- Flame resistant
- Controlled, even unwind
- Meet ROHS & REACH



### Technical Data:

Property	Unit	Typical data	Test Method
Thickness	mm	$0.15 \pm 0.02$	EN 1942
Tensile Strength	N/cm	$\geq 16$	ISO 29864
Elongation	%	$\geq 150$	ISO29864
Adhesion			ISO29862
--- to backing	Oz/19mm	$\geq 1.0$	
--- to steel	N/19mm	$\geq 1.0$	
Flammability		B(self-extinguishing)	ISO3795
Unwind force	N/cm	1.5~4.0	ISO3795
Dielectric Strength	kV/mm	$\geq 40$	IEC60454

Note: The listed values are required only and not intended to serve as product specifications

### Other Property:

Color: Black & Blue

Other sizes and colors are available on request.

### Tape Size:

- ◆ Length: 40m, 48m, 50m, 90m
- ◆ Width: 40mm, 48mm, 50mm
- ◆ Paper Core Inner Dia: 76mm

## **RECOMMENDED USES:**

YONGLE JZ150N Harness Splicing Tape, Use as permanent splice covering wrapping on wiring harness agricultural equipment, aircraft, aerospace and electronic assemblies.

## **STORAGE AND SHELF LIFE**

The shelf life of the product is one year when stored at 20-30 °C , max 65% relative humidity and out of direct sunlight, in original packaging.