

N10 Harness Wrap Tape



High quality PVC Film, coated with a strong rubber based adhesive, hand applicable, 105° C. -25° C application temperature, -40°C operation temperature

FEATURES:

- Rubber adhesive
- PVC carrier

BENEFITS:

- Black and other colors available
- Highly conformable

STANDARD SIZES:

- Length: 25m, 33m
- Width: 9mm, 19mm, 25mm, 50mm
- Core ID: 38mm

COLORS:

- Black • Orange • Gray • White
- Blue • Green • Yellow • Red
- Brown • Violet

*Other sizes and colors are available on request

Properties	Value	Unit	Test Method
Total thickness	0.120±0.02	mm	EN 1942
Tensile strength	>20	N/cm	ISO 29864
Elongation at break	>200	%	ISO 29864
Adhesion strength			ISO 29862
— to steel	>2.2	N/cm	
— to backing	>2.2	N/cm	
Unwind force	1.5~4.0	N/cm	EN 1944
Flammability	B(self-extinguishing)		GMW 16740 / LV 312
Breakdown voltage	5	kV	ASTM D1000
Temperature rating	C:-25~105	°C	GMW 16740 / LV 312

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

Use as permanent wrapping on wiring harnesses for trucks, cars, recreational vehicles, construction equipment, farm implements, aircraft, aerospace and electronic assemblies. Preferred when requirements include long term reliability under varying and extreme environmental conditions.

STORAGE AND SHELF LIFE:

The shelf life of the product is five years when stored at 20-30 ° C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Beijing Huaxia Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.