

Masking Tape (931B)

Applications:

931B masking tape is coated with rubber-based adhesive, it does not have the properties of anti-solvent and anti-UV, and the temperature resistance is 80 °C. It must be used under the premise of not being penetrated by the solvent.

Test Result:

| Property | Unit | Value | Test Method |
|----------------------------|--------|-------------------|-------------|
| Carrier | Paper | | |
| Total Thickness | mm | 0.150 ± 0.005 | ASTM-D-1000 |
| Initial Tack | - | > 12# | ASTM-D-1000 |
| Adhesive Strength to Steel | N/25mm | > 6.5 | ASTM-D-1000 |
| Tensile Strength | N/25mm | > 60 | ASTM-D-1000 |
| Elongation | % | 9-13 | ASTM-D-1000 |
| Cohesion | H/25mm | > 6H | ASTM-D-1000 |
| Temperature Resistance | °C | 80 | ASTM-D-1000 |

Other Property:

- ◆ Color: Beige
- ◆ Shelf life: 12 months when stored in original packing carton at 23°C×65%RH

Tape Size:

- ◆ Standard Roll: 48mm × 33m
- ◆ Paper Core Inner Dia.: 76.2mm

Remarks:

All the data above based on our testing, the user should do trial-application on the above products before coming into application, so as to witness and ensure suitability for user's special purpose and technique.