

JSH150-2 Flexible PVC Marking Tape TDS

Product Overview

JSH150-2 combines practical functionality with robust performance for diverse marking applications. Multiple length options and a balanced color selection address both temporary and permanent marking needs across commercial and industrial sectors.

Performance Data

Property	Value	Test Method
Total Thickness	0.150±0.025 mm	EN 1942
Tensile Strength	≥18 N/cm	ISO 29864
Elongation at Break	≥150%	ISO 29864
Adhesion to Steel	≥1.0 N/cm	ISO 29862
Tack	≥6 #	GB/T 4852

Product Highlights

- **3 Length Options** - Project-specific flexibility (17m, 22m, 33m)
- **Enhanced Durability** - Resists abrasion and chemical exposure
- **Strong Adhesion** - Reliable bonding without residue upon removal
- **Temperature Resistant** - Consistent performance across climate conditions
- **Cost-Effective Solution** - Competitive pricing for budget-sensitive projects

Product Specifications

Standard Lengths: 17m, 22m, 33m

Standard Widths: 48mm, 50mm

Core ID: 77mm

Color Selection: Black, White, Yellow, Red, Blue, Green

Practical Applications

- **Commercial Flooring** - Retail spaces, shopping malls, showrooms
- **Industrial Safety** - Machinery boundaries, walkway delineation
- **Parking Management** - Space numbering, directional arrows
- **Temporary Marking** - Event venues, construction sites
- **Educational Facilities** - Playgrounds, gymnasiums, corridors