

FC150 Colored Harness Wrap Tape

High quality Soft PVC Film, coated with a strong rubber based adhesive, hand applicable, 105° C.

FEATURES:

- Rubber adhesive
- PVC carrier

BENEFITS:

- Black and other colors available
- Highly conformable
- Flame resistant
- Controlled, even unwind
- Meet RoHS & REACH



Technical Data:

Property	Unit	Typical data	Test Method
Total thickness	0.150±0.02	mm	EN1942
Tensile strength	≥16	N/cm	ISO 29864
Elongation at break	≥150	%	ISO 29864
Adhesion strength			ISO 29862
— to steel	≥1.5	N/cm	
— to backing	≥1.5	N/cm	
Unwind force	1.5~4.0	N/cm	EN 1944
Total thickness	0.150±0.02	mm	EN1942
Flammability	B(self-extinguishing)		ISO 3795
Dielectric Strength	≥40	kV/mm	IEC 60454
Temperature rating	B:-25~105	°C	GMW 16740

Note: The listed values are required only and not intended to serve as product specifications

Other Property:

Color: Black White Yellow Red Blue Green

Other sizes and colors are available on request.

Tape Size:

- Length: 30.4m, 33m, 40m
- Width: 19mm, 25mm
- Core ID: 38mm

RECOMMENDED USES:

Use as permanent wrapping on wiring harness agricultural equipment, aircraft, aerospace and electronic assemblies.

Preferred when requirements include need for numerous colors plus long term reliability under varying and extreme environmental conditions.

STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30 °C , max 65% relative humidity and out of direct sunlight, in original packaging.