

8888 PVC dry vinyl loom tape

YONGLE 8888 PVC Dry Vinyl Loom Tape is made of high-quality non-adhesive soft PVC, suitable for manual and mechanical operations. With a temperature rating of -25°C to 85°C, it is specially designed for automotive wire harness wrapping. It delivers reliable performance in vehicle environments, complies with RoHS and REACH standards, and is a premium choice for the automotive wire harness industry.

FEATURES:

PVC carrier

BENEFITS:

- Non-adhesive
- Flame retardant
- Highly conformable
- Soft PVC without adhesive
- Controlled, uniform unwind
- Securely Clings to itself
- Customized to the user's application
- Meet RoHS & REACH



Technical Data:

Property	Unit	Typical data	Test Method
Total Thickness	mm	0.12±0.02	EN 1942
Tensile Strength	N/cm	> 20	ISO 29864
Elongation at break	%	> 250	ISO 29864
Adhesion strength			QCT-906(24fts/min)
---hand taping	Oz/19mm	20-40	
	N/19mm	5.5-11.1	
	Oz/25mm	20-45	
	N/25mm	5.5-12.5	
Flammability	B(self-extinguishing)		GMW 16740/LV 312
Breakdown voltage	kV	5.5	ASTM D1000
Temperature rating	°C	B:-25-85	GMW 16740 / LV 312

Note: The listed values are required only and not intended to serve as product specifications

Other Property:

Color: Black & White & Yellow

Other sizes and colors are available on request.

Tape Size:

- ◆ Length: 33m, 40m
- ◆ Width: 19mm,25mm
- ◆ Paper Core Inner Dia: 38mm

RECOMMENDED USES:

YONGLE 8888 PVC dry vinyl tape, Designed for wrapping applications. For permanent protection of wire harnesses and cables. Also use for insulating and masking parts in the industrial electroplating industry.

STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.